

Package ‘STRINGdb’

September 16, 2016

Type Package

Title STRINGdb (Search Tool for the Retrieval of Interacting proteins database)

Version 1.12.0

Date 2016-03-31

Author Andrea Franceschini <andrea.franceschini@isb-sib.ch>

Maintainer Alexander Roth <alexander.roth@isb-sib.ch>

Description The STRINGdb package provides a R interface to the STRING protein-protein interactions database (<http://www.string-db.org>).

License GPL-2

Depends R (>= 2.14.0)

Imports png, sqldf, plyr, igraph, RCurl, methods, RColorBrewer, gplots, hash, plotrix

Suggests RUnit, BiocGenerics

biocViews Network

NeedsCompilation no

R topics documented:

add_diff_exp_color	3
add_proteins_description	3
benchmark_ppi	4
benchmark_ppi_pathway_view	5
coeffOfvar	6
delColDf	6
diff_exp_example1	7
downloadAbsentFile	7
downloadAbsentFileSTRING	8
get_aliases	8
get_annotations	9
get_annotations_desc	9
get_bioc_graph	10

get_clusters	10
get_enrichment	11
get_graph	11
get_homologs	12
get_homologs_besthits	13
get_interactions	13
get_link	14
get_neighbors	15
get_png	15
get_ppi_enrichment	16
get_ppi_enrichment_full	16
get_proteins	17
get_pubmed	18
get_pubmed_interaction	18
get_STRING_species	19
get_subnetwork	19
get_summary	20
get_term_proteins	20
interactions_example	21
load	22
load_all	22
map	23
mp	23
multi_map_df	24
plot_network	25
plot_ppi_enrichment	25
plot_ppi_enrichment_graph	26
post_payload	27
ppie.compLambda	28
ppie.compLambdaL1L2	29
ppie.compPij	29
ppie.getNumEdgesBetween	30
ppi_enrichment	31
ppi_enrichment_full	31
remove_homologous_interactions	33
renameColDf	33
set_background	34
STRINGdb-class	35
Index	37

add_diff_exp_color *add_diff_exp_color*

Description

Take in input a dataframe containing a logFC column that reports the logarithm of the difference in expression level. Add a "color" column to the data frame such that strongly downregulated genes are colored in green and strong upregulated genes are in red. When the down or up-regulation is instead weak the intensity of the color gets weaker as well, accordingly.

Usage

```
## S4 method for signature 'STRINGdb'  
add_diff_exp_color(screen, logFcColStr="logFC" )
```

Arguments

screen	Dataframe containing the results of the experiment (e.g. the analyzed results of a microarray or RNAseq experiment)
logFcColStr	name of the colum that contains the logFC of the expression

Value

vector containing the colors

Author(s)

Andrea Franceschini

add_proteins_description
add_proteins_description

Description

Add description coluns to the proteins that are present in the data frame given in input. The data frame must contain a column named "STRING_id".

Usage

```
## S4 method for signature 'STRINGdb'  
add_proteins_description(screen)
```

Arguments

screen Dataframe containing the results of the experiment (e.g. the analyzed results of a microarray or RNAseq experiment)

Value

returns the same dataframe given in input with an additional columns containing a description of the proteins.

Author(s)

Andrea Franceschini

benchmark_ppi	<i>benchmark_ppi</i>
---------------	----------------------

Description

benchmark a list of protein-protein interactions using pathways (e.g. KEGG). The function outputs a table where the interactions are mapped to KEGG and the number of TPs and FPs are counted.

Usage

```
## S4 method for signature 'STRINGdb'
benchmark_ppi(interactions_dataframe, pathwayType = "KEGG", max_homology_bitscore = 60, precision_wi
```

Arguments

interactions_dataframe
 a data frame containing the sorted interactions to be benchmarked. The data frame should have the following column names: proteinA, proteinB, score

pathwayType category to use to benchmark the interactions (default KEGG)

max_homology_bitscore
 filter out pairs of homologous proteins, having a similarity bitscore higher than this parameter

precision_window
 define the size of the precision window (i.e. the window used to scan the sorted interactions data frame in order to compute the benchmark precision). At the beginning and at the end of the sorted interactions data frame, the window is automatically enlarged (at the beginning) and reduced (at the end)

exclude_pathways
 Exclude the terms that should not be used for benchmarking. If this parameter is set to "blacklist", a black list to be used maintained by our group is automatically downloaded from our servers (otherwise it is possible to specify a vector with the terms that have to be excluded).

Value

interactions data frame where the interactions are mapped to KEGG and the number of TPs and FPs are counted.

Author(s)

Andrea Franceschini

benchmark_ppi_pathway_view
benchmark_ppi_pathway_view

Description

Takes in input the results of the benchmark_ppi function, and constructs a new table that provides a view at the pathway level (i.e. it list all the pathways to which the interactions belong)

Usage

```
## S4 method for signature 'STRINGdb'
benchmark_ppi_pathway_view(benchmark_ppi_data_frame, precision_threshold=0.2, pathwayType = "KEGG")
```

Arguments

benchmark_ppi_data_frame
 data frame that comes out from the benchmark_ppi function.

precision_threshold
 threshold that specify where to stop taking considering the interactions in the sorted input data frame (the list is scanned until the precision goes below this value).

pathwayType
 the pathway category to use (KEGG by default)

Value

data frame containing the pathways (i.e. terms) of the input proteins. Several parameters are reported: pathway coverage (i.e. number of interactions in the list belonging to the pathway / maximum number of interactions between the pathway proteins (i.e. $\text{proteins} * (\text{proteins}-1)/2$)) total_representation (i.e. number of interactions in the list belonging to the pathway / size of the input data frame)

Author(s)

Andrea Franceschini

coeffOfvar

coeffOfvar

Description

coefficient of variation

Usage

coeffOfvar(x)

Arguments

x input number

Details

coefficient of variation

Value

coefficient of variation

Author(s)Andrea Franceschini

delColDf

delColDf

Description

delete a column in the data frame

Usage

delColDf(df, colName)

Argumentsdf data frame
colName name of the column to be deleted**Value**

data frame

Author(s)

Andrea Franceschini

diff_exp_example1 *example of microarray data (data processed from GEO GSE9008)*

Description

example of microarray data (data processed from GEO GSE9008)

Usage

```
data(diff_exp_example1)
```

Format

Data frames with 20861 observations on the following 3 variables.

gene a character vector

pvalue a numeric vector

logFC a numeric vector

Source

Whyte L, Huang YY, Torres K, Mehta RG. Molecular mechanisms of resveratrol action in lung cancer cells using dual protein and microarray analyses. *Cancer Res* 2007.

downloadAbsentFile *downloadAbsentFile*

Description

download a file only if it is not present.

Usage

```
downloadAbsentFile(urlStr, oD = tempdir())
```

Arguments

urlStr url from which to download the file

oD directory where to store the file

Author(s)

Andrea Franceschini

`downloadAbsentFileSTRING`*downloadAbsentFileSTRING*

Description

download a STRING file only if it is not present or if it is corrupted.

Usage

```
downloadAbsentFileSTRING(urlStr, oD = tempdir())
```

Arguments

<code>urlStr</code>	url from which to download the file
<code>oD</code>	directory where to store the file

Author(s)

Andrea Franceschini

`get_aliases`*get_aliases*

Description

Loads and returns the STRING alias table.

Usage

```
## S4 method for signature 'STRINGdb'  
get_aliases( )
```

Value

a data frame containing the STRING alias table

Author(s)

Andrea Franceschini

get_annotations *get_annotations*

Description

Loads and returns STRING annotations (i.e. GO annotations, KEGG pathways, domain databases). The annotations are stored in the "annotations" variable.

Usage

```
## S4 method for signature 'STRINGdb'  
get_annotations( )
```

Value

a data frame containing the annotations to the STRING proteins (e.g. GeneOntology, KEGG pathways, InterPro domains)

Author(s)

Andrea Franceschini

get_annotations_desc *get_annotations_desc*

Description

Returns a data frame with the description of every STRING annotation term (it downloads and caches the information the first time that is called).

Usage

```
## S4 method for signature 'STRINGdb'  
get_annotations_desc()
```

Value

data frame with the description of every STRING annotation term.

Author(s)

Andrea Franceschini

<code>get_bioc_graph</code>	<i>get_bioc_graph</i>
-----------------------------	-----------------------

Description

Returns the interaction graph as an object of the graph package in Bioconductor.

Usage

```
## S4 method for signature 'STRINGdb'  
get_bioc_graph()
```

Value

interaction graph as an object of the graph package in Bioconductor.

Author(s)

Andrea Franceschini

<code>get_clusters</code>	<i>get_clusters</i>
---------------------------	---------------------

Description

Returns a list of clusters of interacting proteins. See the iGraph (<http://igraph.sourceforge.net/>) documentation for additional information on the algorithms.

Usage

```
## S4 method for signature 'STRINGdb'  
get_clusters(string_ids, algorithm="fastgreedy")
```

Arguments

<code>string_ids</code>	a vector of STRING identifiers.
<code>algorithm</code>	algorithm to use for the clustering. You can choose between "fastgreedy", "walk-trap", "spinglass" and "edge.betweenness").

Value

list of clusters of interacting proteins.

Author(s)

Andrea Franceschini

get_enrichment	<i>get_enrichment</i>
----------------	-----------------------

Description

Returns the enrichment in pathways of the vector of STRING proteins that is given in input.

Usage

```
## S4 method for signature 'STRINGdb'  
get_enrichment(string_ids, category = "Process", methodMT = "fdr", iea = TRUE, minScore=NULL)
```

Arguments

string_ids	a vector of STRING identifiers.
category	category for which to compute the enrichment (i.e. "Process", "Component", "Function", "KEGG", "Pfam", "InterPro"). The default category is "Process".
methodMT	method to be used for the multiple testing correction. (i.e. "fdr", "bonferroni"). The default is "fdr".
iea	specify whether you also want to use electronic inference annotations
minScore	with Tissue and Disease categories is possible to filter the annotations having an annotation score higher than this threshold (from 0 to 5)

Value

Data frame containing the enrichment in pathways of the vector of STRING proteins that is given in input.

Author(s)

Andrea Franceschini

get_graph	<i>get_graph</i>
-----------	------------------

Description

Return an igraph object with the STRING network (for information about igraph visit <http://igraph.sourceforge.net>)

Usage

```
## S4 method for signature 'STRINGdb'  
get_graph()
```

Value

igraph object with the STRING network

Author(s)

Andrea Franceschini

References

Csardi G, Nepusz T: The igraph software package for complex network research, InterJournal, Complex Systems 1695. 2006. <http://igraph.sf.net>

See Also

In order to simplify the most common tasks, we do also provide convenient functions that wrap some iGraph functions. `get_interactions(string_ids)` # returns the interactions in between the input proteins `get_neighbors(string_ids)` # Get the neighborhoods of a protein (or of a vector of proteins) that is given in input. `get_subnetwork(string_ids)` # returns a subgraph from the given input proteins

<code>get_homologs</code>	<i>get_homologs</i>
---------------------------	---------------------

Description

Returns the homologs of the given input identifiers that are present in the given `target_species_id`.

Usage

```
## S4 method for signature 'STRINGdb'
get_homologs(string_ids, target_species_id, bitscore_threshold=NULL)
```

Arguments

```
string_ids      a vector of STRING identifiers.
target_species_id
                 NCBI taxonomy identifier of the species to query for homologs (the species
                 must be present in the STRING database)
bitscore_threshold
                 threshold on the bitscore of the blast alignment.
```

Value

Data frame containing the homologs of the given input identifiers and that are present in the given `target_species_id`.

Author(s)

Andrea Franceschini

get_homologs_besthits *get_homologs_besthits*

Description

Returns the best blast hits x species of the given input identifiers.

Usage

```
## S4 method for signature 'STRINGdb'  
get_homologs_besthits(string_ids, symbets = FALSE, target_species_id = NULL, bitscore_threshold=NULL)
```

Arguments

`string_ids` a vector of STRING identifiers.
`target_species_id` NCBI taxonomy identifier of the species to query for homologs (the species must be present in the STRING database)
`bitscore_threshold` threshold on the bitscore of the blast alignment.
`symbets` specify whether you want only symmetrical best hits

Value

Data frame containing the best blast hits x species of the given input identifiers.

Author(s)

Andrea Franceschini

get_interactions *get_interactions*

Description

Shows the interactions in between the proteins that are given in input.

Usage

```
## S4 method for signature 'STRINGdb'  
get_interactions(string_ids)
```

Arguments

`string_ids` a vector of STRING identifiers

Value

Data frame containing the interactions in between the input proteins.

Author(s)

Andrea Franceschini

<code>get_link</code>	<i>get_link</i>
-----------------------	-----------------

Description

Returns a short link to the network page of our STRING website that shows the protein interactions between the given identifiers.

Usage

```
## S4 method for signature 'STRINGdb'
get_link(string_ids, required_score=NULL, network_flavor="evidence", payload_id = NULL)
```

Arguments

<code>string_ids</code>	a vector of STRING identifiers.
<code>required_score</code>	minimum STRING combined score of the interactions (if left NULL we get the combined score of the object, which is 400 by default).
<code>network_flavor</code>	specify the flavor of the network ("evidence", "confidence" or "actions". default "evidence").
<code>payload_id</code>	an identifier of payload data on the STRING server (see method <code>post_payload</code> for additional informations)

Value

short link to the network page of our STRING website that shows the protein interactions between the input identifiers.

Author(s)

Andrea Franceschini

get_neighbors	<i>get_neighbors</i>
---------------	----------------------

Description

Get the neighborhoods of a protein (or of a vector of proteins) that is given in input.

Usage

```
## S4 method for signature 'STRINGdb'
get_neighbors(string_ids)
```

Arguments

string_ids a vector of STRING identifiers

Value

vector containing the neighborhoods of a protein (or of a vector of proteins) that is given in input.

Author(s)

Andrea Franceschini

get_png	<i>get_png</i>
---------	----------------

Description

Returns a png image of a STRING protein network with the given identifiers.

Usage

```
## S4 method for signature 'STRINGdb'
get_png(string_ids, required_score=NULL, network_flavor="evidence", file=NULL, payload_id=NULL)
```

Arguments

string_ids a vector of STRING identifiers.

required_score minimum STRING combined score of the interactions (if left NULL we get the combined score of the object, which is 400 by default).

network_flavor specify the flavor of the network ("evidence", "confidence" or "actions". default "evidence").

file file where to save the image

payload_id identifier of the payload

Value

Returns a png image of a STRING protein network with the given identifiers.

Author(s)

Andrea Franceschini

`get_ppi_enrichment` *get_ppi_enrichment*

Description

Returns a pvalue representing the enrichment in interactions of the list of proteins (i.e. the probability to obtain such a number of interactions by chance).

Usage

```
## S4 method for signature 'STRINGdb'  
get_ppi_enrichment(string_ids)
```

Arguments

`string_ids` a vector of STRING identifiers

Value

Returns a pvalue representing the enrichment in interactions of the list of proteins (i.e. the probability to obtain such a number of interactions by chance).

Author(s)

Andrea Franceschini

`get_ppi_enrichment_full`
get_ppi_enrichment_full

Description

Returns a vector showing the enrichment in protein interactions in various positions of the list of genes in input. In practice, a list of 3 vectors is returned: 1) enrichment (i.e. enrichment computed in the window from 1 to x) 2) enrichmentWindow (i.e. enrichment computed in a sliding window of size determined by the "edgeWindow" parameters and the sliding steps determined by the "sliceWindow" parameter) 3) enrichmentWindowExtended (i.e. like the enrichmentWindow, but it also includes an initial window of size "windowExtendedReferenceThreshold" with respect to which to compute the enrichment)

Usage

```
## S4 method for signature 'STRINGdb'
get_ppi_enrichment_full(string_ids, sliceWindow = 20, edgeWindow = 140, windowExtendedReferenceThres
```

Arguments

`string_ids` a vector of STRING identifiers

`sliceWindow` defines the interval in proteins after which to compute the enrichment, scanning the list (i.e. the resolution)

`edgeWindow` size of the window that we use to compute the enrichment (i.e. the window pvalue is computed using the proteins inside this "edgeWindow")

`windowExtendedReferenceThreshold` defines the size of a window at the beginning of the list. The enrichment will be computed always including the proteins in this window

`growingWindowLimit` threshold where to stop the computation of the enrichment

Value

Returns a vector showing the enrichment in protein interactions in various positions of the list of genes in input.

Author(s)

Andrea Franceschini

get_proteins *get_proteins*

Description

Returns the STRING proteins data frame. (it downloads and caches the information the first time that is called).

Usage

```
## S4 method for signature 'STRINGdb'
get_proteins()
```

Value

STRING proteins data frame.

Author(s)

Andrea Franceschini

<code>get_pubmed</code>	<i>get_pubmed</i>
-------------------------	-------------------

Description

Returns vector with the PUBMED IDs of the publications that contain the names of the proteins in the input vector.

Usage

```
## S4 method for signature 'STRINGdb'  
get_pubmed(string_ids)
```

Arguments

`string_ids` a vector of STRING identifiers

Value

vector with the PUBMED IDs of the publications that contain the names of the proteins in the input vector.

Author(s)

Andrea Franceschini

<code>get_pubmed_interaction</code>	<i>get_pubmed_interaction</i>
-------------------------------------	-------------------------------

Description

Returns vector with the PUBMED IDs of the publications that contain the names of both the input proteins.

Usage

```
## S4 method for signature 'STRINGdb'  
get_pubmed_interaction(STRING_id_a, STRING_id_b )
```

Arguments

`STRING_id_a` STRING identifier
`STRING_id_b` STRING identifier

Value

vector with the PUBMED IDs of the publications that contain the names of both the input proteins.

Author(s)

Andrea Franceschini

get_STRING_species *get_STRING_species*

Description

Returns a data frame with the species (i.e. organisms) that are present in STRING.

Usage

```
get_STRING_species(version=NULL, species_name=NULL)
```

Arguments

version STRING version
species_name name of the species that you are searching

Value

data frame with the species (i.e. organisms) that are present in STRING.

Author(s)

Andrea Franceschini

get_subnetwork *get_subnetwork*

Description

Returns the subgraph generated by the given input proteins.

Usage

```
## S4 method for signature 'STRINGdb'  
get_subnetwork(string_ids )
```

Arguments

string_ids a vector of STRING identifiers

Value

Returns the subgraph (i.e. an iGraph object) generated by the given input proteins.

Author(s)

Andrea Franceschini

<code>get_summary</code>	<code>get_summary</code>
--------------------------	--------------------------

Description

Returns a summary of the STRING sub-network containing the identifiers provided in input.

Usage

```
## S4 method for signature 'STRINGdb'  
get_summary(string_ids)
```

Arguments

`string_ids` a vector of STRING identifiers

Value

Returns a summary (i.e. a text description) of the STRING sub-network containing the identifiers provided in input.

Author(s)

Andrea Franceschini

<code>get_term_proteins</code>	<code>get_term_proteins</code>
--------------------------------	--------------------------------

Description

Returns the proteins annotated to belong to a given term.

Usage

```
## S4 method for signature 'STRINGdb'  
get_term_proteins(term_ids, string_ids=NULL, enableIEA=TRUE)
```

Arguments

term_ids	vector of terms
string_ids	a vector of STRING identifiers. If the variable is set, the method returns only the proteins that are present in this vector.
enableIEA	whether to consider also Electronic Inferred Annotations

Value

Returns the proteins annotated to belong to a given term.

Author(s)

Andrea Franceschini

interactions_example *example of a protein-protein interactions sorted data frame*

Description

example of a sorted list of protein-protein interactions, resulta our cooccurrence algorithm (SVD_Phy)

Usage

```
data(interactions_example)
```

Format

Data frames with 20861 observations on the following 3 variables.

proteinA a character vector

proteinB a character vector

score a numeric vector

load	<i>load</i>
------	-------------

Description

Downloads and returns the STRING network (the network is set also in the graph variable of the STRING_db object).

It makes use of the variables: "backgroundV" vector containing STRING identifiers to be used as background (i.e. the STRING network loaded will contain only the proteins that are present also in this vector) "score_threshold" STRING combined score threshold (the network loaded contains only interactions having a combined score greater than this threshold)

Usage

```
## S4 method for signature 'STRINGdb'  
load()
```

Value

STRING network (i.e. an iGraph object. For info look to <http://igraph.sourceforge.net>)

Author(s)

Andrea Franceschini

load_all	<i>load_all</i>
----------	-----------------

Description

Force download and loading of all the files (so that you can later store the object on the hard disk if you like). It makes use of the variables: "backgroundV" vector containing STRING identifiers to be used as background (i.e. the STRING network loaded will contain only the proteins that are present also in this vector) "score_threshold" STRING combined score threshold (the network loaded contains only interactions having a combined score greater than this threshold)

Usage

```
## S4 method for signature 'STRINGdb'  
load_all()
```

Author(s)

Andrea Franceschini

map	<i>map</i>
-----	------------

Description

Maps the gene identifiers of the input dataframe to STRING identifiers. It returns the input dataframe with the "STRING_id" additional column.

Usage

```
## S4 method for signature 'STRINGdb'
map(my_data_frame, my_data_frame_id_col_names, takeFirst=TRUE, removeUnmappedRows=FALSE, quiet=FALSE)
```

Arguments

<code>my_data_frame</code>	data frame provided as input.
<code>my_data_frame_id_col_names</code>	vector containing the names of the columns of "my_data_frame" that have to be used for the mapping.
<code>takeFirst</code>	boolean indicating what to do in case of multiple STRING proteins that map to the same name. If TRUE, only the first of those is taken. Otherwise all of them are used. (default TRUE)
<code>removeUnmappedRows</code>	remove the rows that cannot be mapped to STRING (by default those lines are left and their STRING_id is set to NA).
<code>quiet</code>	Setting this variable to TRUE we can avoid printing the warning relative to the unmapped values.

Value

Returns the dataframe that is given in input with the "STRING_id" additional column.

Author(s)

Andrea Franceschini

mp	<i>mp</i>
----	-----------

Description

Maps the gene identifiers of the input vector to STRING identifiers (using a take first approach). It returns a vector with the STRING identifiers of the mapped proteins.

Usage

```
## S4 method for signature 'STRINGdb'
mp(protein_aliases)
```

Arguments

protein_aliases
vector of protein aliases that we want to convert to STRING identifiers

Value

It returns a vector with the STRING identifiers of the mapped proteins.

Author(s)

Andrea Franceschini

multi_map_df	<i>multi_map_df</i>
--------------	---------------------

Description

mapping function (it add the possibility to map using more than one column of the data frame)

Usage

```
multi_map_df(dfToMap, dfMap, strColsFrom, strColFromDfMap, strColToDfMap, caseSensitive=FALSE)
```

Arguments

dfToMap	input data frame (that contains the columns that need to be mapped)
dfMap	data frame containing the mapping data
strColsFrom	sorted vector containing the names of the columns to be used in the input data frame for the mapping (the order of the elements in the vector defines the priority for the mapping)
strColFromDfMap	name of the column in the mapping data frame to be used as source for the mapping
strColToDfMap	name of the column in the mapping data frame to be used as target for the mapping
caseSensitive	specify whether the mapping should be case sensitive

Value

data frame with an additional column containing the result of the mapping

Author(s)

Andrea Franceschini

plot_network	<i>plot_network</i>
--------------	---------------------

Description

Plots an image of the STRING network with the given proteins.

Usage

```
## S4 method for signature 'STRINGdb'
plot_network(string_ids, payload_id=NULL, required_score=NULL, add_link=TRUE, add_summary=TRUE)
```

Arguments

string_ids	a vector of STRING identifiers
payload_id	an identifier of payload data on the STRING server (see method post_payload for additional informations)
required_score	a threshold on the score that overrides the default score_threshold, that we use only for the picture
add_link	parameter to specify whether you want to generate and add a short link to the relative page in STRING. As default this option is active but we suggest to deactivate it in case one is generating many images (e.g. in a loop). Deactivating this option avoids to generate and store a lot of short-urls on our server.
add_summary	parameter to specify whether you want to add a summary text to the picture. This summary includes a p-value and the number of proteins/interactions.

Author(s)

Andrea Franceschini

plot_ppi_enrichment	<i>plot_ppi_enrichment</i>
---------------------	----------------------------

Description

Plots a graph showing the enrichment in protein interactions in various positions of the list of genes in input.

Usage

```
## S4 method for signature 'STRINGdb'
plot_ppi_enrichment(string_ids, file=NULL, sliceWindow = 20, edgeWindow = 140,
                    windowExtendedReferenceThreshold = 260, minVal=0.000000001, title="",
```

Arguments

<code>string_ids</code>	a vector of STRING identifiers
<code>file</code>	file where to save the graph as an image
<code>sliceWindow</code>	defines the interval in proteins after which to compute the enrichment, scanning the list (i.e. the resolution)
<code>edgeWindow</code>	size of the window that we use to compute the enrichment (i.e. the window pvalue is computed using the proteins inside this "edgeWindow")
<code>windowExtendedReferenceThreshold</code>	defines the size of a window at the beginning of the list. The enrichment will be computed always including the proteins in this window
<code>title</code>	title of the graph.
<code>minVal</code>	minimum value that the pvalue can assume in the log-scale graph. If the p-value is lower, we convert the value to this minimum value
<code>quiet</code>	if set to TRUE the method runs in quiet mode (turning off any output message)

Author(s)

Andrea Franceschini

`plot_ppi_enrichment_graph`
plot_ppi_enrichment_graph

Description

Plots a graph showing the enrichment in protein interactions in various positions of the list of genes in input.

Usage

```
plot_ppi_enrichment_graph(proteins, ppi_network, file, sliceWindow, edgeWindow, windowExtendedRefere
```

Arguments

<code>proteins</code>	a vector of protein identifiers
<code>ppi_network</code>	an igraph object containing the protein-protein interactions' graph.
<code>file</code>	file where to save the graph as an image

sliceWindow	defines the interval in proteins after which to compute the enrichment, scanning the list (i.e. the resolution)
edgeWindow	size of the window that we use to compute the enrichment (i.e. the window pvalue is computed using the proteins inside this "edgeWindow")
windowExtendedReferenceThreshold	defines the size of a window at the beginning of the list. The enrichment will be computed always including the proteins in this window
title	title of the graph.
minVal	minimum value that the pvalue can assume in the log-scale graph. If the p-value is lower, we convert the value to this minimum value
quiet	if set to TRUE the method runs in quiet mode (turning off any output message)

Author(s)

Andrea Franceschini

References

Pradines JR, Farutin V, Rowley S, Dancik V. Analyzing protein lists with large networks: edge-count probabilities in random graphs with given expected degrees. *J. Comput. Biol.* 2005;12:113-128. Franceschini, A et al. (2013). STRING v9.1: protein-protein interaction networks, with increased coverage and integration. In: *Nucleic Acids Res.* 2013 Jan;41(Database issue)

post_payload	<i>post_payload</i>
--------------	---------------------

Description

Posts the input to STRING and returns an identifier that you can use to access the payload when you enter in our website.

Usage

```
## S4 method for signature 'STRINGdb'
post_payload(stringIds, colors=NULL, comments=NULL, links=NULL, iframe_urls=NULL, logo_imgF=NULL, leg
```

Arguments

stringIds	vector of STRING identifiers.
colors	vector containing the colors to use for a every STRING identifier (the order of the elements must match those in the string_ids vector)
comments	vector containing the comments to use for every STRING identifier (the order of the elements must match those in the string_ids vector)
links	vector containing the links to use for every STRING identifier (the order of the elements must match those in the string_ids vector)

<code>iframe_urls</code>	vector containing the urls of the iframes to use for every STRING identifier (the order of the elements must match those in the <code>string_ids</code> vector).
<code>logo_imgF</code>	path to a file containing the logo image to be display in the STRING website
<code>legend_imgF</code>	path to a file containing a legend image to be display in the STRING website

Value

identifier of the payload.

Author(s)

Andrea Franceschini

`ppie.compLambda` *ppie.compLambda*

Description

compute the number of expected interactions between a set of proteins.

Usage

```
ppie.compLambda(degrees, edgeNum)
```

Arguments

<code>degrees</code>	vector containing the degrees of the nodes of a set of proteins
<code>edgeNum</code>	total number of edges of the entire graph

Value

number of expected interactions

Author(s)

Andrea Franceschini

References

Pradines JR, Farutin V, Rowley S, Dancik V. Analyzing protein lists with large networks: edge-count probabilities in random graphs with given expected degrees. *J. Comput. Biol.* 2005;12:113-128. Franceschini, A et al. (2013). STRING v9.1: protein-protein interaction networks, with increased coverage and integration. In: *Nucleic Acids Res.* 2013 Jan;41(Database issue)

ppie.compLambdaL1L2 *ppie.compLambdaL1L2*

Description

Compute lambda L1L2

Usage

`ppie.compLambdaL1L2(degreesI, degreesJ, edgeNum)`

Arguments

degreesI vector containing the degrees of the nodes present in nodeSet I
degreesJ vector containing the degrees of the nodes present in nodeSet J
edgeNum total number of edges of the entire graph

Details

compute the number of expected interactions between two sets of nodes

Author(s)

Andrea Franceschini

ppie.compPij *ppie.compPij*

Description

Compute the pvalue of protein I to interact with protein J (look at the Pradines paper referenced below)

Usage

`ppie.compPij(degI, degJ, edgeNum)`

Arguments

degI degree of protein I
degJ degree of protein J
edgeNum total number of edges of the entire graph

Value

return the pvalue of protein I to interact with protein J (look at the Pradines paper referenced below)

Author(s)

Andrea Franceschini

References

Pradines JR, Farutin V, Rowley S, Dancik V. Analyzing protein lists with large networks: edge-count probabilities in random graphs with given expected degrees. *J. Comput. Biol.* 2005;12:113-128. Franceschini, A et al. (2013). STRING v9.1: protein-protein interaction networks, with increased coverage and integration. In: *Nucleic Acids Res.* 2013 Jan;41(Database issue)

`ppie.getNumEdgesBetween`

ppie.getNumEdgesBetween

Description

find the number of interactions between two sets of nodes

Usage

```
ppie.getNumEdgesBetween(graph, nodesFrom, nodesTo)
```

Arguments

graph	igraph object
nodesFrom	list of nodes
nodesTo	list of nodes

Value

return the number of interactions between two sets of nodes

Author(s)

Andrea Franceschini

ppi_enrichment *ppi_enrichment*

Description

Computes the enrichment in protein-protein interactions.

Usage

```
ppi_enrichment(hitList, ppi_network)
```

Arguments

hitList	sorted list of proteins (from the most significant to the least significant)
ppi_network	an igraph object containing the graph of the protein-protein interaction's network.

Value

enrichment	pvalue that describes the probability to get such a number of interactions by chance
lambda	expected number of interactions

Author(s)

Andrea Franceschini

References

Pradines JR, Farutin V, Rowley S, Dancik V. Analyzing protein lists with large networks: edge-count probabilities in random graphs with given expected degrees. *J. Comput. Biol.* 2005;12:113-128. Franceschini, A et al. (2013). STRING v9.1: protein-protein interaction networks, with increased coverage and integration. In: *Nucleic Acids Res.* 2013 Jan;41(Database issue)

ppi_enrichment_full *ppi_enrichment_full*

Description

Compute the enrichment in protein-protein interactions of a sorted list of proteins. The computation is repeated at different positions in the list.

Usage

```
ppi_enrichment_full(hitList, ppi_network, sliceWindow, edgeWindow, windowExtendedReferenceThreshold,
```

Arguments

hitList	sorted list of proteins (from the most significant to the least significant)
ppi_network	an igraph object containing the protein-protein interactions' graph.
sliceWindow	defines the interval in proteins after which to compute the enrichment, scanning the list (i.e. the resolution)
edgeWindow	size of the window that we use to compute the enrichment (i.e. the window pvalue is computed using the proteins inside this "edgeWindow")
windowExtendedReferenceThreshold	when we compute the "windowExtended" pvalue we are computing the pvalue that considers the following interactions: 1) the interactions inside the edgeWindow (as we do with the edgeWindow pvalue) 2) the interactions that connects the proteins in the edgeWindow with the proteins in another window at the beginning of the list (i.e. the windowExtendedReference). windowExtendedReferenceThreshold defines the size of this windowExtendedReference window. In this way we can compute, in a reliable way, the enrichment of a sorted list of proteins, in various positions of the list.
growingWindowLimit	stop to compute the enrichment (from position 1 to position n) after growingWindowLimit proteins in the sorted list. (this limit speeds up the computation of the 2 other types of enrichment)
quiet	if set to TRUE the method runs in quiet mode (turning off any output message)

Value

enrichment	vector containing the enrichments in protein-protein interactions of the input list of genes (the length of the vector is $\text{length}(\text{hitList})/\text{sliceWindow}$).
enrichmentWindow	vector containing the enrichments in protein-protein interactions of the input list of genes (the length of the vector is $\text{length}(\text{hitList})/\text{sliceWindow}$). The enrichment is computed considering only the proteins inside the sliding window
enrichmentWindowExtended	vector containing the enrichments in protein-protein interactions of the input list of genes (the length of the vector is $\text{length}(\text{hitList})/\text{sliceWindow}$). Look at the description of the windowExtendedReferenceThreshold variable

Author(s)

Andrea Franceschini

References

Pradines JR, Farutin V, Rowley S, Dancik V. Analyzing protein lists with large networks: edge-count probabilities in random graphs with given expected degrees. *J. Comput. Biol.* 2005;12:113-128. Franceschini, A et al. (2013). STRING v9.1: protein-protein interaction networks, with increased coverage and integration. In: *Nucleic Acids Res.* 2013 Jan;41(Database issue)

```
remove_homologous_interactions  
    remove_homologous_interactions
```

Description

With this method it is possible to remove the interactions that are composed by a pair of homologous/similar proteins, having a similarity bitscore between each other higher than a threshold.

Usage

```
## S4 method for signature 'STRINGdb'  
remove_homologous_interactions(interactions_dataframe, bitscore_threshold = 60)
```

Arguments

```
interactions_dataframe  
    a data frame containing the sorted interactions to be benchmarked. The data  
    frame should have the following column names: proteinA, proteinB, score  
bitscore_threshold  
    filter out pairs of homologous proteins, having a similarity bitscore higher than  
    this parameter
```

Value

interactions data frame where the homologous pairs have been removed, from the input interactions' data frame

Author(s)

Andrea Franceschini

```
renameColDf    renameColDf
```

Description

Rename a column of a data frame

Usage

```
renameColDf(df, colOldName, colNewName)
```

Arguments

df	input data frame
colOldName	column name to be changed
colNewName	new column name

Value

data frame with the column name changed

Author(s)

Andrea Franceschini

set_background	<i>set_background</i>
----------------	-----------------------

Description

With this method you can specify a vector of proteins to be used as background. The network is reloaded and only the proteins that are present in the background vector are inserted in the graph. Besides, the background is taken in consideration for all the enrichment statistics.

Usage

```
## S4 method for signature 'STRINGdb'  
set_background(background_vector )
```

Arguments

background_vector	vector of STRING protein identifiers
-------------------	--------------------------------------

Author(s)

Andrea Franceschini

STRINGdb-class	Class "STRINGdb"
----------------	------------------

Description

The R package STRINGdb provides a convenient interface to the STRING protein-protein interactions database for the R/bioconductor users. Please look at the manual/vignette to get additional information and examples on how to use the package. STRING is a database of known and predicted protein-protein interactions. It contains information from numerous sources, including experimental repositories, computational prediction methods and public text collections. Each interaction is associated with a combined confidence score that integrates the various evidences. STRING is regularly updated, the latest version 9.05 contains information on 5 millions proteins from more than 1100 species. The STRING web interface is freely accessible at: <http://string-db.org/>

Extends

All reference classes extend and inherit methods from "[envRefClass](#)".

Fields

annotations: Object of class data.frame ~~
 annotations_description: Object of class data.frame ~~
 graph: Object of class igraph ~~
 proteins: Object of class data.frame ~~
 speciesList: Object of class data.frame ~~
 species: Object of class numeric ~~
 version: Object of class character ~~
 input_directory: Object of class character ~~
 backgroundV: Object of class vector ~~
 score_threshold: Object of class numeric ~~

Methods

set_background(background_vector): ~~
 post_payload(stringIds, colors, comments, links, iframe_urls, logo_imgF, legend_imgF):
 ~~
 plot_network(string_ids, payload_id, required_score): ~~
 plot_ppi_enrichment(string_ids, file, sliceWindow, edgeWindow, windowExtendedReferenceThreshold, mi):
 ~~
 map(my_data_frame, my_data_frame_id_col_names, takeFirst, removeUnmappedRows, quiet):
 ~~
 load(): ~~
 get_term_proteins(term_ids, string_ids, enableIEA): ~~

```

get_summary(string_ids): ~~
get_subnetwork(string_ids): ~~
get_ppi_enrichment_full(string_ids, sliceWindow, edgeWindow, windowExtendedReferenceThreshold, grow
~~
get_ppi_enrichment(string_ids): ~~
get_proteins(): ~~
get_png(string_ids, required_score, network_flavor, file, payload_id): ~~
get_neighbors(string_ids): ~~
get_link(string_ids, required_score, network_flavor, payload_id): ~~
get_interactions(string_ids): ~~
get_homologs_besthits(string_ids, symbets, target_species_id, bitscore_threshold):
~~
get_homologs(string_ids, target_species_id, bitscore_threshold): ~~
get_graph(): ~~
get_enrichment(string_ids, category, methodMT, iea): ~~
get_clusters(string_ids, algorithm): ~~
get_annotations_desc(): ~~
get_annotations(): ~~
load_all(): ~~
initialize(...): ~~
add_proteins_description(screen): ~~
add_diff_exp_color(screen, logFcColStr): ~~
show(): ~~

```

Author(s)

Andrea Franceschini

References

Franceschini, A (2013). STRING v9.1: protein-protein interaction networks, with increased coverage and integration. In: 'Nucleic Acids Res. 2013 Jan;41(Database issue):D808-15. doi: 10.1093/nar/gks1094. Epub 2012 Nov 29'.

See Also

<http://stitch-db.org>

Examples

```
showClass("STRINGdb")
```

Index

*Topic **classes**

STRINGdb-class, [35](#)

*Topic **datasets**

diff_exp_example1, [7](#)

interactions_example, [21](#)

add_diff_exp_color, [3](#)

add_proteins_description, [3](#)

benchmark_ppi, [4](#)

benchmark_ppi_pathway_view, [5](#)

coeff0fvar, [6](#)

delColDf, [6](#)

diff_exp_example1, [7](#)

downloadAbsentFile, [7](#)

downloadAbsentFileSTRING, [8](#)

envRefClass, [35](#)

get_aliases, [8](#)

get_annotations, [9](#)

get_annotations_desc, [9](#)

get_bioc_graph, [10](#)

get_clusters, [10](#)

get_enrichment, [11](#)

get_graph, [11](#)

get_homologs, [12](#)

get_homologs_besthits, [13](#)

get_interactions, [13](#)

get_link, [14](#)

get_neighbors, [15](#)

get_png, [15](#)

get_ppi_enrichment, [16](#)

get_ppi_enrichment_full, [16](#)

get_proteins, [17](#)

get_pubmed, [18](#)

get_pubmed_interaction, [18](#)

get_STRING_species, [19](#)

get_subnetwork, [19](#)

get_summary, [20](#)

get_term_proteins, [20](#)

interactions_example, [21](#)

load, [22](#)

load_all, [22](#)

map, [23](#)

mp, [23](#)

multi_map_df, [24](#)

plot_network, [25](#)

plot_ppi_enrichment, [25](#)

plot_ppi_enrichment_graph, [26](#)

post_payload, [27](#)

ppi_enrichment, [31](#)

ppi_enrichment_full, [31](#)

ppie.compLambda, [28](#)

ppie.compLambdaL1L2, [29](#)

ppie.compPij, [29](#)

ppie.getNumEdgesBetween, [30](#)

remove_homologous_interactions, [33](#)

renameColDf, [33](#)

set_background, [34](#)

STRINGdb (STRINGdb-class), [35](#)

STRINGdb-class, [35](#)